

Hisense

HM388

8" Point of Sale Tablet



8" Tablet for Point of Sale Applications

The Hisense HM388 Windows tablet can be used as cost effective hand held terminal for line busting, by waitresses for table side order entry and by store clerks for assisting customers on the floor. The included docking / charging station includes a serial and USB ports that can be used to control a variety of peripherals when the tablet is used as a budget-friendly stationary workstation.

The 8 inch, bezel-free and wide screen display is designed with Projected Capacitive (PCAP) touch technology that helps to extend the operating life and allow multi-touch gesture control. Use the ports in the included docking station to connect to a wide range of peripheral devices.

- 8" Wide Screen
- Bezel-Free, PCAP Multi-Touch Screen
- Standard Integrated Card Reader
- Standard Docking Station Includes I/O Expansion Ports



HM388 – 8" Point of Sale Tablet



Stylish, Space-Saving Tablet Includes Docking Station



Integrated Card Reader Standard



Standard Docking Station Includes I/O Expansion Ports

Features

- Front and Rear Cameras
- Integrated Card Reader
- 0.8 Watt Speaker
- LED Indicator
- Built-In Microphone Provides Sound Input While Making Web-Calls
- Capture a Front View Picture or Record Videos
- HM388 Tablet Includes a Built-In Battery
- Docking Station Includes Power Adaptor and Cord
- Compatible with Popular Standard Applications

Specifications

HM388

Processor:	Cherrytrail Z8350
Operating System:	Windows 10
Display:	8" TFT LCD (LED Back-Light)
Resolution:	1280 x 800
Brightness:	300 cd/m2
Touch Panel:	True-Flat Projected Capacitive Touch
Memory:	2GB RAM
Storage:	32GB eMMC
Camera –	Rear: 5 Megapixel Camera Front: 0.3 Megapixel Camera
Wireless –	Wi-Fi: WiFi802.11 b/g/n 2.4GHz Bluetooth: Integrated Bluetooth V4.0
Speaker:	8 Ohm, 0.8 Watt Speaker
Audio:	3.5mm Socket
MCR:	Standard Integrated Triple Track Card Reader
NFC:	Supports MIFARE one and MIFARE CPU Card
Battery –	Type: 400mAh (3.8V) Life: 4 Hours
I/O Interface:	Micro-SD Slot / Micro-USB / Audio / Micro HDMI 1.4a
Tablet Connector:	7 Pin Pogo Style Connector
Docking Station –	I/O: Three USB 2.0 / COM (RJ48) DC Input: One DC Jack (5V)
Power Supply:	5V / 3A External Power Adaptor 100-240V 50/60Hz
Temperature –	Operating: 32° F to 104° F (0° C to 40° C) Storage: -4° F to 149° F (-20° C to 65° C)
Humidity –	Operating: 20% to 90% RH (Non-Condensing) Storage: 20% to 93% RH (Non-Condensing)
Dimensions –	Tablet: 9"W x 4-13/16"H x 1/2"D Tablet/Docking Station: 9"W x 8"H x 4-1/2"D
Safety and EMI:	FCC Class-B / CE Class-B / RoHS

Camera | Charging Indicator



Micro SD Card Slot

Speaker | Volume – | Volume + | Power | Camera



MCR | DC Jack | COM (RJ48) | USB | HDMI | Micro USB | DC Jack | Audio